

AMPIET 28 Features	
<b>Chassis</b>	
Easy Access Enclosure	<input checked="" type="checkbox"/>
Easy Maneuver 5th Wheel Steering	<input checked="" type="checkbox"/>
Easy Pull 12" ( 305mm) Wheels	<input checked="" type="checkbox"/>
Tow Bar Activated Braking	Adjustable
Engine/ Generator Mounting	4X Extreme Duty Rubber Isolators
Heavy Duty Lunette Eye Hitch	<input checked="" type="checkbox"/>
Tie Down Rings	2 Front / 2 Rear
<b>Control Panel</b>	
Intuitive Digital Controller	<input checked="" type="checkbox"/>
Full Digital Instrumentation	(8 Performance Readings)
Battery Volts	<input checked="" type="checkbox"/>
Water Temperature	<input checked="" type="checkbox"/>
Oil Pressure	<input checked="" type="checkbox"/>
Fuel Level	<input checked="" type="checkbox"/>
Tachometer	<input checked="" type="checkbox"/>
Hour Meter	<input checked="" type="checkbox"/>
Output Amps	<input checked="" type="checkbox"/>
Output Volts	<input checked="" type="checkbox"/>
Trouble Shooting Display	<input checked="" type="checkbox"/>
Number Wiring	<input checked="" type="checkbox"/>
<b>Engine</b>	
Engine Perkins 1104D Series TIII	T3 (121 hp)
Engine Perkins 1104D Series T4F	T4 (74 hp)
Turbocharged	<input checked="" type="checkbox"/>
Delayed Stop Turbo Protection	<input checked="" type="checkbox"/>
Long Life 1800 RPM Speed	<input checked="" type="checkbox"/>
Engine Over speed Protection	<input checked="" type="checkbox"/>
Full Flow Fuel Filter	<input checked="" type="checkbox"/>
Full Flow Lubricating Oil Filter	<input checked="" type="checkbox"/>
Muffler	<input checked="" type="checkbox"/>
Engine Diagnostics	<input checked="" type="checkbox"/>
Engine Preheater	Optional
Low Oil Pressure Shut Down Switch	<input checked="" type="checkbox"/>
High Temp Water SDS	<input checked="" type="checkbox"/>
Air Intake Restriction Indicator	<input checked="" type="checkbox"/>
Low Coolant Level Shutdown	Optional
Fuel Types	Diesel / Jet A
Starting	12V 1000 Amp Hr. Battery
Perkins Full Time and Mileage Warranty	2 Years or 2000 hours
	* Low Sulfur Diesel only on Tier 4
<b>Power / Generator</b>	
Marathon Generator	25KW 31KVA @ .8 PF
Brushless	<input checked="" type="checkbox"/>
Output Performance Continuous	850 Amps
Output Performance Peak 5 Seconds	2000 Amps Peak
Adjustable Current	300-2000 Amps
Line Drop Compensation	Automatic @28.5V
Protection	Over/Under
DC output switch	<input checked="" type="checkbox"/>
Meets Compliance Standard	MIL-STD-704E
Power Output Cable 30 feet	MIL-C-5756
<b>Operating Environment</b>	
Temperature	-22° to 122°F ( -30° to +50°C)
High Altitude Performance	Turbo Charged
<b>Safety</b>	
E-Stop	<input checked="" type="checkbox"/>
On Board Fire Extinguisher	Optional
Towing Beacon	<input checked="" type="checkbox"/>
Night Reflectors	All Sides - Outlining Corners
Sound Suppression	Enclosure Walls and Doors
Parking Brake	Tow Bar - Adjustable
<b>Fuel</b>	
Fuel Tank Size (Large)	26 US Gal (97L)
Extended Run Time	>11hrs @ 800 Amps
Low Fuel	Automatic Shutdown
Low Fuel Warning	<input checked="" type="checkbox"/>
Fuel Gauge on Instrument Panel	<input checked="" type="checkbox"/>
<b>Dimensions</b>	
Weight	3090 lbs. (1402kg)
Height	64" (1575mm)
Length	101" (2565mm)
Width	76" (1930mm)
Turning Radius	202" (5131mm )
<b>Options</b>	
Extra Long 50' Power Output Cable	Option
120VAC power	Option
Water Circulation Block Heater	Option
Battery Blanket	Option
Forklift Pockets	Option
Galvanized Chassis, Stainless Enclosure	Option
Telematics (GPS/GSM)(Cell/Network link)	Option
Extreme Cold Weather Kit	Option
12 Volt Output	Option
Maintenance Beacon	Option
Corner Bumpers	Option
Custom Colors	Option
<b>Coatings</b>	
Paint	Zinc Primer
Paint Type	Automotive Grade Top Coat
Standard Colors	White / Black
<b>Worry Free</b>	
Warranty	2 Years
Engine Warranty	2 Years or 2000 hrs.
Satisfaction Guarantee	
Designed and Assembled in Canada	